

## Technische Information

| DN         | Zoll       | Innen<br>Ø | Außen - Ø | Wandstärke<br>des<br>PVC-Rohres | Außen - Ø<br>über<br>Kiesbelag | Kiesbelag-<br>stärke | Gewicht   |
|------------|------------|------------|-----------|---------------------------------|--------------------------------|----------------------|-----------|
| mm         |            | mm         | mm        | mm                              | ca. mm                         | mm                   | ca. kg/ m |
| <b>35</b>  | <b>1¼"</b> | 34,5       | 41,5      | 3,5                             | 63                             | 10,5                 | 3,1       |
| <b>40</b>  | <b>1½"</b> | 41         | 48        | 3,5                             | 75                             | 13,5                 | 4,8       |
| <b>50</b>  | <b>2"</b>  | 52         | 60        | 4,0                             | 92                             | 16,0                 | 6,1       |
| <b>80</b>  | <b>3"</b>  | 80         | 88        | 4,0                             | 121                            | 16,5                 | 10,0      |
| <b>100</b> | <b>4"</b>  | 103        | 113       | 5,0                             | 143                            | 15,0                 | 11,5      |
| <b>115</b> | <b>4½"</b> | 115        | 125       | 5,0                             | 157                            | 16,0                 | 13,5      |
| <b>125</b> | <b>5"</b>  | 127        | 140       | 6,5                             | 172                            | 16,0                 | 15,14     |
| <b>150</b> | <b>6"</b>  | 150        | 165       | 7,5                             | 196                            | 15,5                 | 16,5      |
| <b>175</b> | <b>7"</b>  | 178        | 195       | 8,5                             | 226                            | 15,5                 | 23,0      |
| <b>200</b> | <b>8"</b>  | 205        | 225       | 10,0                            | 261                            | 18,0                 | 30,0      |
| <b>250</b> | <b>10"</b> | 255        | 280       | 12,5                            | 316                            | 18,0                 | 41,0      |
| <b>300</b> | <b>12"</b> | 301        | 330       | 14,5                            | 366                            | 16,0                 | 48,5      |
| <b>350</b> | <b>14"</b> | 365        | 400       | 17,5                            | 436                            | 18,0                 | 65,0      |
| <b>400</b> | <b>16"</b> | 411        | 450       | 19,5                            | 482                            | 16,0                 | 74,0      |

**Werkstoff :** PVC-hart nach DIN 4925

|                        |         |                  |           |                |
|------------------------|---------|------------------|-----------|----------------|
| <b>Schlitzweiten :</b> | Körnung | <b>0,7 - 1,2</b> | <b>Sw</b> | <b>0,75 mm</b> |
|                        | Körnung | <b>1 - 2</b>     | <b>Sw</b> | <b>1,0 mm</b>  |
|                        | Körnung | <b>2 - 3</b>     | <b>Sw</b> | <b>1,5 mm</b>  |
|                        | Körnung | <b>3 - 5</b>     | <b>Sw</b> | <b>2,0 mm</b>  |

**Verbindung :** nach DIN 4925

|                    |                        |             |
|--------------------|------------------------|-------------|
| <b>Baulängen :</b> | DN 35, 40, 50          | <b>1,0m</b> |
|                    | DN 80 - DN 400         | <b>2,0m</b> |
|                    | (1m-Baulängen möglich) |             |